

Back Bars



The "green" products in our range are marked with this logo:



We hope you will enjoy our catalogue and look forward to cooperating with you.



Back Bars

The Back Bar Chillers presented in this section are available in different heights and with 1, 2 or 3 doors (solid or glass). The BA20 and BA30 with glass door can be supplied with either hinged or sliding doors.

They are now available with black or stainless steel exterior. If you choose the black version, we now offer a new variant with aluminium door frame.

The Counter Bottle Coolers can be supplied with a combination of cupboards and drawers according to the customers needs.

The elegant design of both back bar display and counter chillers makes them suitable for bars and restaurants and can easily be combined.

Stainless steel mirror polished interior can be supplied for all BA and CBC models.

» Back Bars



BA5H

- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves
- Adjustable feet



BA15H

- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves
- Adjustable feet



BA25H

- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 2 Adjustable shelves
- Adjustable feet

Technical specifications

Model	BA5H	BA15H	BA25H	BA25S
Climate Class	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	100	122	191	191
Net Volume, l	94	116	183	183
Cans, 330 ml	138	161	270	240
Cans, 500 ml	96	112	188	168
Bottles, 330 ml	-	-	-	-
Bottles, 1,5 l PET	-	-	-	-
External Dimensions, WxDxH	500x520x870	600x520x870	900x520x870	900x515x870
Internal Dimensions, WxDxH	410x350x720	510x350x720	810x350x720	810x350x720
Doors	1 hinged glass	1 hinged glass	2 hinged glass	2 sliding glass
Shelves/Baskets	2, 398x335	2, 498x335	4, 330x395	4, 330x395
Outer Body	Black	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	210	210	230	230
Energy Consumption, kWh/24h				
Gross Weight, kg	46	48	66,4	66,4
Net Weight, kg	44	46	64,4	64,4
Noise Level dbA	45	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N	N
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	76	76	140	140
Internal Light	LED	LED	LED	LED
Option: Charged with R600a				

» Back Bars



BA20S

- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 4 Adjustable shelves
- Adjustable feet



BA30S-2


- Interior LED light
- Fan assisted cooling
- 2 Double glazed doors
- 2 Adjustable shelves behind each door
- Door holders for easier loading of cabinet
- Adjustable feet



BA30S-3

- Interior LED light
- Fan assisted cooling
- 3 Double glazed doors
- 2 Adjustable shelves behind each door
- Door holders for easier loading of cabinet
- Adjustable feet

Technical specifications

Model	BA20S	BA30S-2	BA30S-3
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	196	328	328
Net Volume, l	188	320	320
Cans, 330 ml	240	380	380
Cans, 500 ml	168	266	266
Bottles, 330 ml	156	240	240
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	900x515x900	1355x515x900	1355x515x900
Internal Dimensions, WxDxH	805x345x730	1257x345x730	1257x345x730
Doors	2 sliding glass	2 sliding glass	3 sliding glass
Shelves/Baskets	4, 330x395	4, 405x365	6, 405x365
Outer Body	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	230	260	260
Energy Consumption, kWh/24h			
Gross Weight, kg	67,4	94	95
Net Weight, kg	65,4	91	92
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N
Refrigerant	R134a	R134a	R134a
Charge, g	140	186	186
Internal Light	LED	LED	LED
Option: Charged with R600a			

» Back Bars



BA10H

- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves
- Adjustable feet



BA20H

- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 4 Adjustable shelves
- Adjustable feet



BA30H

- Interior LED light
- Fan assisted cooling
- 3 Double glazed doors
- 2 Adjustable shelves behind each door
- Adjustable feet

Technical specifications

Model	BA10H	BA20H	BA30H
Climate Class	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	124	196	328
Net Volume, l	118	188	320
Cans, 330 ml	161	270	425
Cans, 500 ml	112	188	296
Bottles, 330 ml	96	156	240
Bottles, 1,5 l PET	-	-	-
External Dimensions, WxDxH	600x520x900	900x520x900	1355x520x900
Internal Dimensions, WxDxH	508x355x732	805x345x730	1257x345x730
Doors	1 hinged glass	2 hinged glass	3 hinged glass
Shelves/Baskets	2, 496x350	4, 330x395	6, 405x365
Outer Body	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	210	230	260
Energy Consumption, kWh/24h			
Gross Weight, kg	49	67,4	94,6
Net Weight, kg	47	65,4	91,6
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N
Refrigerant	R134a	R134a	R134a
Charge, g	76	140	186
Internal Light	LED	LED	LED
Option: Charged with R600a			